



HOS RED ROCK

HOSMAX300 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	292 ft 0 in (89.0 m)	Beam:	64 ft 0 in (19.5 m)	Draft Max:	19 ft 11 in (6.07 m)
Gross:	3,911 GT	Net:	1,173 NT	Draft Min:	11 ft 3 in (3.43 m)
IMO:	9647655	O.N.:	1244591	Flag:	U.S.
Certifications:	Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, FFFV-1, (E), +A1, +ACCU, +AMS, OSV, ENVIRO, GP, UWILD, ACP, CRC, OSR-C2				

PERFORMANCE

Cruise Speed:	10.0 kts	133 gal/hr (503 l/hr)	Max Speed:	12.0 kts	208 gal/hr (787 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-----------------------

PROPULSION, MACHINERY AND STEERING

Main Engines:	4 x Caterpillar 3516C	Total Rating:	7,300 kW
Main Propulsion:	2 x Schottel Azimuthing Z-Drives	Propeller Diameter:	106 in (2,692 mm)
Bow Thruster:	2 x Schottel FPP Tunnel	Total Rating:	6,700 hp
		Total Rating:	3,160 hp
		Power Generation:	690V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	5,391 LT (5,477 MT)	Deck Area:	197 ft x 55 ft (10,835 ft ²) 60.0 m x 16.8 m (1,006.6 m ²)
Deck Cargo:	3,350 LT (3,404 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	14,347 ft ³ (406 m ³)	System Pressure:	80 psi (5.5 bar)
Liquid Mud:	20,846 bbl (3,314 m ³)	Discharge Rate:	1,000 GPM (227 m ³ /hr)
Methanol:	1,605 bbl (255 m ³)	Discharge Rate:	250 GPM (57 m ³ /hr)
Potable Water:	57,494 gal (218 m ³)	Watermaker Cap.:	2,000 USG/day
Rig Fuel:	220,168 gal (833 m ³)	Discharge Rate:	750 GPM (170 m ³ /hr)
Rig Water:	498,523 gal (1,887 m ³)	Discharge Rate:	750 GPM (170 m ³ /hr)
Cooler Area:	600 ft ³ (17 m ³)	Freezer Area:	400 ft ³ (11 m ³)

ELECTRONICS

AIS, Anemometer, Auto Pilot, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VERIPOS, VHF Radio, VHF Radio (Handheld), VSAT, X-band Radar

ACCOMMODATIONS

17 air conditioned/heated staterooms certified for 50 person berthing.

SPECIAL FEATURES

Oil Spill Recovery:	ABS Capability Class 2	Recovered Oil Capacity:	19,241 bbl (3,059 m ³) (>60 °C FP) 1,605 bbl (255 m ³) (<60 °C FP)
Off-ship Firefighting:	ABS FIFI 1	Number of Fire Monitors:	2
Deck Crane:	1 x Appleton EB70-53-33	Total Flow Rate:	10,568 gal/min (2,402 m ³ /hr)
		Max Lift @ Max Radius:	3 MT @ 53 ft
		Max Lift @ Min Radius:	13 MT @ 16 ft
		Personnel Rating:	0.6 MT

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.