

HOS SWEET WATER

240EDQ Offshore Supply Vessel



an ath.	240 ft 0 in (73			54 ft 0 in (16.5 m)		IFORMATION 14 ft 10 in (4.52 m	
<u>ength:</u>		5.2 m)	Beam:	54 π 0 in (16.5 m) 580 NT	Draft Max:		1)
<u>iross:</u>	1,934 GT		<u>Net:</u>		Draft Min:	8 ft 0 in (2.44 m)	
<u>MO:</u>	9495545 Oceans-SOLA	c	<u>O.N.:</u>	31015892321	<u>Flag:</u>	Mexico	
ertifications:			Chinning II	DPS-2, (E), +A1, +AN		C 2	
lassifications:	Loaunne, Anne		Shipping, +i	JF3-2, (E), +A1, +A1	13, ACC, O3V, O3K	-C2	
				PERFOR	MANCE		
Cruise Speed:	10.0 kts 1	14 gal/hr (431 l,	′hr) <u>M</u>	ax Speed: 13.0	kts 167 gal/hr	(632 l/hr)	
		P	ROPULS	SION, MACH	INERY AND	STEERING	
<u>Main Engines:</u>		2 x Caterpi	llar 3516C		Tot	al Horsepower:	4,000 hp
Propellers:		CPP, High	Efficiency, 4-	Blade	Pro	peller Diameter:	95 in (2,413 mm)
rimary Genera	ators:	3 x Caterpi	llar C 18		<u>Tot</u>	al Rating:	1,020 kW
<u> Bow Thruster:</u>		2 x Brunvo	l CPP Tunne	I	<u>Tot</u>	tal Rating:	1,900 hp
Stern Thruster: 1 x Brunvoll CPP Tunnel			I	<u>Tot</u>	al Rating:	950 hp	
Rudder:	Independent Steering, Schilling Fishtail				Pov	wer Generation:	480V/60 Hz/3-Phase
			CAP	ACITIES AND	DELIVERY	RATES	
Deadweight:		2,701 LT (2,744 MT)		Deck Area:		176 ft x 45 ft (7,920 ft ²)	
							53.6 m x 13.7 m (735.8 m²)
<u> Deck Cargo:</u>		1,800 LT (1,829 MT)		De	eck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk: 6,240 ft ³ (17			177 m³)		<u>Sy</u>	<u>stem Pressure:</u>	80 psi (5.5 bar)
Brine: 8,251 bbl (l (1,312 m³)		<u>Di</u>	<u>scharge Rate:</u>	407 GPM (93 m³/hr)
Liquid Mud: 8,251 bbl ((1,312 m³)		<u>Di</u>	scharge Rate:	407 GPM (93 m³/hr)
otable Water.		30,850 ga	(117 m³)			-	
Recovered Oil (<u>>60 deg C F</u>	P): 8,251 bbl	(1,312 m³)				
<u>Rig Fuel:</u>	-	107,650 g	al (407 m³)		Di	<u>scharge Rate:</u>	550 GPM (125 m³/hr)
Rig Water:		317,479 g	al (1,202 m³)		Di	scharge Rate:	550 GPM (125 m³/hr)
Cooler Area: 850 ft ³ (24 m ³)					Fre	eezer Area:	850 ft ³ (24 m ³)
<mark>Off-ship Firefig</mark>	hting Monit	ors: 1			<u>To</u>	tal Flow Rate:	3,000 gal/min (682 m³/hr)
				ELECTI	RONICS		
						C I I I I	Control, L-3 NMS 6000, Mag Comp

ACCOMMODATIONS

11 air conditioned/heated staterooms certified for 24 person berthing.

SPECIAL FEATURES

Deck Crane:

1 x Hyrda-Pro HP48-20T

 Max Lift @ Max Radius:
 3 MT @ 48 ft

 Max Lift @ Min Radius:
 18 MT @ 10 ft

 Moon Pool:
 36 in. dia.

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.

Hornbeck Offshore